

<i>Description</i>	Non-Rechargeable, Lithium Manganese Dioxide Battery.
<i>National Stock Number</i>	6135-01-455-9646
<i>For Use In</i>	SDU-5/E, ACR-4F, ACR-4G, Distress Lights.
<i>Replacement for</i>	BA-1574/U (Mercury Battery)
<i>Nominal Dimensions</i>	Diameter: 0.665 in (17 mm) Length: 2.375 in (60 mm)
<i>Nominal Weight</i>	2.0 oz (56.7 g)
<i>Nominal Voltage</i>	6.0 V
<i>Nominal Capacity</i>	1.4 Ah
<i>Operating Voltage</i>	6.0 V
<i>Cutoff Voltage</i>	3.6 V
<i>Operating Temperature Range</i>	-20°C to +55°C (-4°F to +131°F)
<i>Storage Temperature Range</i>	-40°C to +55°C (-40°F to +131°F)
<i>Operational Life</i>	22Hr when used in the SDU-5/E Distress Light.
<i>Case Material</i>	Black Plastic sleeve.
<i>Case Color</i>	Black #37038 per FED-STD-595 with White Printing.
<i>Connector</i>	Threaded Brass (+) cap.
<i>Shelf Life</i>	After (5)Yr of storage @ 21 ⁰ C, 50% RH) remaining capacity will be greater than 97%.
<i>Disposal</i>	Discharge through 100 ohm 1/2% watt resistor to (0) V before discarding. Environmentally Safe. Check with local regulations for proper disposal.
<i>Packaging</i>	Unit Box 1per, Master Box 240 per Weight: 50 lb (22.72 Kg); Cubes .83 ft ³ (.029 m ³)

WHEN ORDERING SPECIFY P/N:
BT-70430

