

<i>Description</i>	Non-Rechargeable Alkaline Manganese Dioxide Battery.
<i>For Use In</i>	Various electronic applications.
<i>Nominal Dimensions</i>	Length: 2.00 in (51 mm) Height: 1.89 in (48 mm) Width: .352 in (9 mm)
<i>Nominal Weight</i>	0.138 Lb (0.62 Kg)
<i>Nominal Voltage</i>	9.0 V
<i>Nominal Capacity</i>	550 mAh
<i>Cutoff Voltage</i>	5.4 V
<i>Operating Temperature Range</i>	-20°C to +55°C (-4°F to +131°F)
<i>Storage Temperature Range</i>	-40°C to +55°C (-40°F to +131°F)
<i>Case Material</i>	ABS (Acrylonitrile Butadiene Styrene) Plastic.
<i>Case Color</i>	Black with embossed printing.
<i>Terminal Contacts</i>	Flat Nickel Plated Steel contacts.
<i>Shelf Life</i>	4 Yr to 85% initial capacity when stored @ 20°C (68°F) 50% RH. 5 Yr to 85% initial capacity when stored @ 4°C (39°F) 50% RH.
<i>Disposal</i>	Environmentally Safe - Contains Zero (0)% Mercury. Check with local regulations for proper disposal.
<i>Packaging</i>	Unit Box 1 per, Master Box 405 per Weight: 64 lb (29.09 Kg); Cubes: 0.53 ft ³ (0.014 m ³)

WHEN ORDERING SPECIFY P/N:
BT-70192-1

