

## BA-5390/U

(NSN-6135-01-501-0833)

(An alternative for the  
BA-5590/U: NSN-6135-01-036-3495)



System:	Non-Rechargeable Lithium/Manganese Dioxide Battery
Part No:	UB0001
Nominal Voltage:	30 Volts or 15 Volts
Capacity (C):	11 AHrs @ 250 mA to 20V or 22 AHrs @ 250 mA to 10V @ 23°C
Max. Discharge:	2 Amps continuous series 4 Amps continuous parallel
Weight:	1300 grams max.
Oper. Temp. Range:	-30°C to 72°C
Storage Temp. Range:	-40°C to 95°C
Volume:	883 cm <sup>3</sup>
Connector:	SC-C-179492
Housing:	Hard plastic case
Cells:	Hermetic Ni-Plated Steel Cans
Transportation:	Class 9

For a complete description of transportation regulations and definitions of the transportation classifications "Excepted" and Class 9," refer to Ultralife's web site at:

[http://www.ulbi.com/whitepapers/Ultralife\\_Batteries\\_Lithium\\_Battery\\_Transportation\\_Regulations.pdf](http://www.ulbi.com/whitepapers/Ultralife_Batteries_Lithium_Battery_Transportation_Regulations.pdf)

